

VANGUARD SITE

110V EMERGENCY BULKHEAD

Vanguard Site delivers safe site illumination in the event of a power failure. Featuring a sleek, shallow profile and carefully designed lens for improved spacings, Vanguard Site also has configurable maintained or non-maintained operation and now features selectable Self Test / Manual Test operation. With a hinged gear tray for easy and rapid installation and reliable LiFePO4 batteries, the Vanguard Site is the only 110V Emergency bulkhead you need.



Features

- Selectable Self Test / Manual test operation
- Hinged gear tray for quick and easy installation
- Selectable maintained or non-maintained operation
- 3 hours emergency duration
- Supplied with self adhesive exit legend kit

Specification

Code	Description	Lumen Output	Emergency Lumen Output	Wattage	Efficacy
VANS/3Y/ST	Vanguard Site 110V M/NM EM Bulkhead 3Hr IP66 Selectable ST/M	150lm	150 lm	3W	

Product Information

Warranty	5 Years
Emergency Battery Warranty	5 Years
Colour Appearance (CCT)	6500K
IP Rating	IP66
IK Rating	IK08
Emergency Battery Type	LiFePO4
Voltage	110V

Colour Finish	Yellow RAL1007
LED Life Expectancy	L70B50 54,000 Hours
Power Factor	0.3
Frequency	50/60Hz
Driver Type	Fixed Output
Approval	UKCA CE
Electrical Class	Class II

Tel: 0114 279 8999 | Email: sales@redarrowelectrical.co.uk | redarrowelectrical.co.uk

Red Arrow Electrical Ltd, Cortonwood Drive, Brampton, Barnsley, S73 0UF

Material (Body/Housing)	ABS
Material (Diffuser/Cover)	Polycarbonate
Colour Rendition (CRI)	Ra >80

Working Temperature	0°C to 45°C
EM Working Temperature	0°C to 45°C



SITE LIGHTING

SPECIFICATION SHEET

VANGUARD SITE

110V EMERGENCY BULKHEAD

Packaging Information

Dimensions (mm)	L: 351 x W: 111 x D: 63 mm
Product Net Weight (kg)	0.49 kg
Barcode	5055807628204
Box Dimensions (mm)	L: 357 x W: 115 x D: 70 mm
Box Gross Weight (kg)	0.59 kg

Units/Outer Carton	10
Outer Carton Barcode	15055807628201
Outer Carton Dimensions (mm)	L: 605 x W: 375 x D: 155 mm
Outer Carton Gross Weight (kg)	6.7 kg

