

WEATHERGUARD SITE FLEX & JUNCTION BOX

IP65 NON-CORROSIVE FITTINGS C/W FLEX & JUNCTION BOX

For fast and efficient installation, Weatherguard Site is also available pre-wired with 1m of cable and junction box. Save time and money on site.



Features

- Pre-wired with 1m cable and junction box
- Fast and easy to install
- High efficacy - 100lm/W
- Unique, future proof replaceable LED module
- Stainless steel diffuser clips as standard

Specification

Code	Description	Lumen Output	Emergency Lumen Output	Wattage	Efficacy
WGS220Y-E/PC	Weatherguard Site 600mm c/w Flex & Junction Box & 3HR Emergency	2000lm	263 lm	20W	100 lm/W

Product Information

Warranty	3 Years
Emergency Battery Warranty	3 Years
Colour Appearance (CCT)	4000K
IP Rating	IP65
IK Rating	IK07
Emergency Battery Type	LiFePO4
Voltage	110V
Material (Body/Housing)	Polycarbonate
Material (Diffuser/Cover)	Polycarbonate
Colour Rendition (CRI)	Ra >80

Colour Finish	Yellow RAL1007
LED Life Expectancy	L70B50 30,000 Hours
Power Factor	0.5
Frequency	50/60Hz
Driver Type	Fixed Output
Approval	UKCA CE
Electrical Class	Class I
Working Temperature	0°C to 40°C
EM Working Temperature	0°C to 40°C

WEATHERGUARD SITE FLEX & JUNCTION BOX

IP65 NON-CORROSIVE FITTINGS C/W FLEX & JUNCTION BOX

Packaging Information

Dimensions (mm)	L: 664 x W: 103 x D: 78mm
Product Net Weight (kg)	1.45 kg
Barcode	5055807622738
Box Dimensions (mm)	L: 810 x W: 110 x D: 80 mm
Box Gross Weight (kg)	1.5 kg

Units/Outer Carton	9
Outer Carton Barcode	15055807622735
Outer Carton Dimensions (mm)	L: 825 x W: 340 x D: 260 mm
Outer Carton Gross Weight (kg)	14.1 kg

