

UPLIGHT

WORKSPACE LIGHTING

This innovative 110V Uplight features a high lumen output and 360° light distribution, making it an efficient solution for Site Lighting.



Features

- Efficient 360° light distribution
- High light output, ideal for large spaces
- Emergency version, switchable for prevent discharge during storage
- Aux socket for interlinking or power tools
- Convenient carry strap



Specification

Code	Description	Lumen Output	Emergency Lumen Output	Wattage	Efficacy
ULE72YPW	Uplight Emergency c/w 3m cable + plug	7920lm	350 lm	72W	110 lm/W

Product Information

Warranty	2 Years
Emergency Battery Warranty	2 Years
Colour Appearance (CCT)	6500K
IP Rating	IP54
IK Rating	IK07
Emergency Battery Type	LiFePO4
Voltage	110V
Material (Body/Housing)	ABS
Material (Diffuser/Cover)	Polycarbonate
Colour Rendition (CRI)	Ra >80

Colour Finish	Yellow RAL1007
LED Life Expectancy	L70B50 35,000 Hours
Power Factor	0.9
Frequency	50Hz
Driver Type	Fixed Output
Approval	UKCA CE
Electrical Class	Class I
Working Temperature	0°C to 40°C
EM Working Temperature	0°C to 40°C

UPLIGHT

WORKSPACE LIGHTING

Packaging Information

Dimensions (mm)	L: 1330 x D: 820 mm
Product Net Weight (kg)	3.1 kg
Barcode	5055807620475

Box Dimensions (mm)	L: 1345 x W: 182 x D: 160 mm
Box Gross Weight (kg)	3.9 kg

