

# WEATHERGUARD SITE FLEX & JUNCTION BOX

## IP65 NON-CORROSIVE FITTINGS C/W FLEX & JUNCTION BOX

For fast and efficient installation, Weatherguard Site is also available pre-wired with 1m of cable and junction box. Save time and money on site.



### Features

- Pre-wired with 1m cable and junction box
- Fast and easy to install
- High efficacy - 100lm/W
- Unique, future proof replaceable LED module
- Stainless steel diffuser clips as standard



### Specification

| Code       | Description                                      | Lumen Output | Emergency Lumen Output | Wattage | Efficacy |
|------------|--------------------------------------------------|--------------|------------------------|---------|----------|
| WGS525Y/PC | Weatherguard Site 1500mm c/w Flex & Junction Box | 2500lm       |                        | 25W     | 100 lm/W |

### Product Information

|                           |               |
|---------------------------|---------------|
| Warranty                  | 3 Years       |
| Colour Appearance (CCT)   | 4000K         |
| IP Rating                 | IP65          |
| IK Rating                 | IK07          |
| Voltage                   | 110-240V      |
| Material (Body/Housing)   | Polycarbonate |
| Material (Diffuser/Cover) | Polycarbonate |
| Colour Rendition (CRI)    | Ra >80        |

|                     |                     |
|---------------------|---------------------|
| Colour Finish       | Yellow RAL1007      |
| LED Life Expectancy | L70B50 30,000 Hours |
| Power Factor        | 0.9                 |
| Frequency           | 50/60Hz             |
| Driver Type         | Fixed Output        |
| Approval            | UKCA CE             |
| Electrical Class    | Class I             |
| Working Temperature | -25°C to 40°C       |

|                                |                            |
|--------------------------------|----------------------------|
| <b>Dimensions (mm)</b>         | L: 1562 x W: 72 x D: 78mm  |
| <b>Product Net Weight (kg)</b> | 1.72 kg                    |
| <b>Barcode</b>                 | 5055807623636              |
| <b>Box Dimensions (mm)</b>     | L: 1707 x W: 98 x D: 80 mm |
| <b>Box Gross Weight (kg)</b>   | 2.2 kg                     |

|                                       |                              |
|---------------------------------------|------------------------------|
| <b>Units/Outer Carton</b>             | 9                            |
| <b>Outer Carton Barcode</b>           | 15055807623633               |
| <b>Outer Carton Dimensions (mm)</b>   | L: 1725 x W: 310 x D: 255 mm |
| <b>Outer Carton Gross Weight (kg)</b> | 20.4 kg                      |

