

WEATHERGUARD SITE TRIPOD HEAD

IP65 NON-CORROSIVE FITTINGS C/W TRIPOD HEADS & TRIPOD

Weatherguard Site tripod mounted fittings offer ultimate flexibility on site. The heads are supplied ready to mount onto the tripod, complete with 2x110V power outlets and 5m of cable.



Features

- Fast and easy to set up on site
- Fitted with twin 110V sockets
- Pre-wired with 5m cable and plug
- IP65 and IK07 rated
- Unique, future proof replaceable LED module



Specification

Code	Description	Lumen Output	Emergency Lumen Output	Wattage	Efficacy
WGS525Y-E/TH	Weatherguard Site Tripod Head 1200mm c/w 3HR Emergency	2500lm	225 lm	25W	100 lm/W

Product Information

Warranty	3 Years
Emergency Battery Warranty	3 Years
Colour Appearance (CCT)	4000K
IP Rating	IP65
IK Rating	IK07
Emergency Battery Type	LiFePO4
Voltage	110V
Material (Body/Housing)	Polycarbonate
Material (Diffuser/Cover)	Polycarbonate
Colour Rendition (CRI)	Ra >80

Colour Finish	Yellow RAL1007
LED Life Expectancy	L80B50 30,000 Hours
Power Factor	0.9
Frequency	50/60Hz
Driver Type	Fixed Output
Approval	UKCA CE
Electrical Class	Class I
Working Temperature	0°C to 40°C
EM Working Temperature	0°C to 40°C

WEATHERGUARD SITE TRIPOD HEAD

IP65 NON-CORROSIVE FITTINGS C/W TRIPOD HEADS & TRIPOD

Packaging Information

Dimensions (mm)	L: 1562 x W: 72 x D: 78mm
Product Net Weight (kg)	3.72 kg
Barcode	5055807622752

Box Dimensions (mm)	L: 1580 x W: 200 x D: 120 mm
Box Gross Weight (kg)	4.27 kg

