

WEATHERGUARD SITE A-FRAME

IP65 NON-CORROSIVE FITTINGS C/W PLASTER'S A-FRAME

Our Plasterer's A-Frame is a handy addition to the Weatherguard Site range. This portable fitting is easy to relocate and features a useful cable storage facility



Features

- Delivers light where it is required
- Lightweight and easy to relocate on site
- Strong, stable frame
- Supplied with 5m cable and pre-wired plug
- Includes 2x 110V power outlets for connecting more fittings or power tools



Specification

Code	Description	Lumen Output	Emergency Lumen Output	Wattage	Efficacy
WGS220Y-E/AF	Weatherguard Site A-Frame c/w 3HR Emergency	2000lm	180 lm	20W	100 lm/W

Product Information

Warranty	3 Years
Emergency Battery Warranty	3 Years
Colour Appearance (CCT)	4000K
IP Rating	IP65
IK Rating	IK07
Emergency Battery Type	LiFePO4
Voltage	110V
Material (Body/Housing)	Polycarbonate, Steel Frame & Polypropylene Socket
Material (Diffuser/Cover)	Polycarbonate
Colour Rendition (CRI)	Ra >80

Colour Finish	Yellow RAL1007
LED Life Expectancy	L80B50 30,000 Hours
Power Factor	0.9
Frequency	50/60Hz
Driver Type	Fixed Output
Approval	UKCA CE
Electrical Class	Class I
Working Temperature	0°C to 40°C
EM Working Temperature	0°C to 40°C

WEATHERGUARD SITE A-FRAME

IP65 NON-CORROSIVE FITTINGS C/W PLASTER'S A-FRAME

Packaging Information

Dimensions (mm)	L: 880 x W: 305 mm
Product Net Weight (kg)	3.3 kg
Barcode	5055807622776

Box Dimensions (mm)	800 x 225 x 155mm
Box Gross Weight (kg)	3.75 kg

