

360° TOWERLIGHT HEAD

HIGH OUTPUT DIRECTIONAL OPEN AREA FLOODLIGHT

This robust, innovative, 110V floodlight features a high lumen output of 84,000lm and 360° light distribution. The Towerlight also can be linked to two additional heads for extra coverage, making it an incredibly efficient solution for site lighting.



Features

- High Output, Ideal for Large spaces
- 3m Telescopic Aluminium Tripod
- 6500K
- 3 Year Warranty



Specification

Code	Description	Lumen Output	Emergency Lumen Output	Wattage	Efficacy
TWL360-600	360 TowerLight 600W Head	84000lm		600W	140 lm/W

Product Information

Warranty	3 Years
Colour Appearance (CCT)	6500K
IP Rating	IP65
IK Rating	IK10
Voltage	100-240V
Material (Body/Housing)	Aluminium
Material (Diffuser/Cover)	Polycarbonate
Colour Rendition (CRI)	Ra >80

Colour Finish	Yellow RAL1007
Power Factor	0.9
Frequency	50/60Hz
Driver Type	Dimmable
Approval	UKCA CE
Electrical Class	Class I
Working Temperature	-20°C to 45°C

360° TOWERLIGHT HEAD

HIGH OUTPUT DIRECTIONAL OPEN AREA FLOODLIGHT

Packaging Information

Dimensions (mm)	L: 286 x W: 298 x D: 435 mm
Product Net Weight (kg)	17.62 kg
Barcode	5055807626354
Box Dimensions (mm)	L: 330 x W: 300 x D: 505 mm
Box Gross Weight (kg)	17.62 kg

Units/Outer Carton	1
Outer Carton Barcode	5055807626354
Outer Carton Dimensions (mm)	L: 330 x W: 300 x D: 505 mm
Outer Carton Gross Weight (kg)	17.62 kg

