

COMET SITE

SLIM 110V FLOODLIGHTS

The Comet Site floodlight offers a wide range of outputs. The product is supplied with a 1-metre pre-wired rubber cable and a U-shaped mounting bracket, making Comet Site an extremely cost-effective solution.



Features

- IP65
- IK07
- 3 Year Warranty
- U shaped Mounting Bracket



Specification

Code	Description	Lumen Output	Emergency Lumen Output	Wattage	Efficacy
CMT50Y	Comet Site Floodlight 50W 5000lm 4000K IP65 Yellow	5000lm		50W	100 lm/W

Product Information

Warranty	3 Years
Colour Appearance (CCT)	4000K
IP Rating	IP65
IK Rating	IK07
Voltage	110V
Material (Body/Housing)	Aluminum
Material (Diffuser/Cover)	Glass
Colour Rendition (CRI)	Ra >80

Colour Finish	Yellow RAL1007
LED Life Expectancy	L70B50 50,000 Hours
Power Factor	>0.9
Frequency	50/60Hz
Driver Type	Fixed Output
Approval	UKCA CE
Electrical Class	Class I
Working Temperature	-30°C to 45°C

COMET SITE

SLIM 110V FLOODLIGHTS

Packaging Information

Dimensions (mm)	L: 212 x W: 216 x D: 32 mm
Product Net Weight (kg)	0.846 kg
Barcode	5055807625753
Box Dimensions (mm)	L:220 x W: 40 x D: 205 mm
Box Gross Weight (kg)	0.9 kg

Units/Outer Carton	10
Outer Carton Barcode	15055807625750
Outer Carton Dimensions (mm)	L: 456 x W: 226 x D: 225 mm
Outer Carton Gross Weight (kg)	9.7 kg

