

FESTOON

110V EXTENDABLE FESTOONS

Our Connectable Festoon Kit range now includes 12m, 22m and 50m lengths. All kits use our unique connector and can be joined in any combination, up to a total length of 150m. This makes extending the festoon on site simple and easy, saving time and money.



Features

- Designed in the UK by Red Arrow
- Extendable up to 150m long
- Robust, high efficiency LED heads
- Pre-wired with industrial 3 pin plug
- IK07 rated for site applications

Specification

Code	Description	Lumen Output	Emergency Lumen Output	Wattage	Efficacy
FKF50100W	Festoon Kit Connectable 20-Way 50m	11000lm		100W	110 lm/W

Product Information

Warranty	2 Years
Colour Appearance (CCT)	6000K
IP Rating	IP44
IK Rating	IK07
Voltage	110V
Material (Body/Housing)	Polycarbonate
Material (Diffuser/Cover)	Polycarbonate
Colour Rendition (CRI)	Ra >80

Colour Finish	Yellow RAL1007
LED Life Expectancy	L70B50 35,000 Hours
Power Factor	0.9
Frequency	50Hz
Driver Type	Fixed Output
Approval	UKCA CE
Electrical Class	Class I
Working Temperature	-20°C to 40°C

FESTOON

110V EXTENDABLE FESTOONS

Packaging Information

Dimensions (mm)	L: 50m Head: H: 60 x Ø: 75 mm
Product Net Weight (kg)	4.4 kg
Barcode	5055807624367
Box Dimensions (mm)	L: 340 x W: 340 x D: 160 mm
Box Gross Weight (kg)	9.4 kg

Units/Outer Carton	2
Outer Carton Barcode	15055807624364
Outer Carton Dimensions (mm)	L: 700 x W: 355 x D: 180 mm
Outer Carton Gross Weight (kg)	10.3 kg

