







## Orthomat® Standard

Quickly tackle standing fatigue in dry workplaces



- Versatile single layer foam anti-fatigue mat.
- Insulates standing workers against the effects of cold concrete floors.
- Lightweight, so easy to transport and reposition.
- Best suited to dry environments.
- High visibility version available with bright yellow borders.
- Textured surface provides attractive appearance.
- Available in mats and rolls.
- Ideal for lighter industrial use where the user doesn't turn regularly in a static position.
- Fire tested to BS EN 13501-1.



Styles Available

Black

Grey

Safety

## Parts

| Part Number | Size                     | Colour       | Weight (kg) |
|-------------|--------------------------|--------------|-------------|
| AF070903    | 0.9 m x 3 m              | Black/Yellow | 4.8         |
| AF010903    | 0.9 m x 3 m              | Black        | 4.8         |
| AF010003C   | 0.9 m x per linear metre | Black        | 1.6         |
| AF010003    | 0.9 m x 18.3 m           | Black        | 40          |
| AF010002    | 0.9 m x 1.5 m            | Black        | 3.27        |
| AF010706C   | 1.2 m x per linear metre | Black/Yellow | 2.1         |
| AF010706    | 1.2 m x 18.3 m           | Black/Yellow | 70          |
| AF010703C   | 0.9 m x per linear metre | Black/Yellow | 3.01        |
| AF060003C   | 0.9 m x per linear metre | Grey         | 2           |
| AF060003    | 0.9 m x 18.3 m           | Grey         | 40          |
| AF060002    | 0.9 m x 1.5 m            | Grey         | 3.27        |
| AF010702    | 0.9 m x 1.5 m            | Black/Yellow | 3.27        |
| AF010701    | 0.6 m x 0.9 m            | Black/Yellow | 1.31        |
| AF010005C   | 1.2 m x per linear metre | Black        | 2.1         |
| AF010001    | 0.6 m x 0.9 m            | Black        | 1.31        |
| AF010703    | 0.9 m x 18.3 m           | Black/Yellow | 40          |
| AF060001    | 0.6 m x 0.9 m            | Grey         | 1.31        |
| AF010005    | 1.2 m x 18.3 m           | Black        | 58.55       |

## Technical Specifications

|                                                                |                                                                 |
|----------------------------------------------------------------|-----------------------------------------------------------------|
| <b>Material</b>                                                | Open Cell PVC (Foam)                                            |
| <b>Surface Finish</b>                                          | Pebble                                                          |
| <b>Product Height</b>                                          | 9.5 mm                                                          |
| <b>Roll Length</b>                                             | 18.3 m                                                          |
| <b>Size of Safety Border</b>                                   | 100 mm                                                          |
| <b>Min. Operating Temperature</b>                              | 0°C                                                             |
| <b>Max. Operating Temperature</b>                              | +60°C                                                           |
| <b>Environmental Resistance</b>                                | Suitable for dry indoor environments                            |
| <b>Typical Applications</b>                                    | Production lines, Assembly areas, Packing stations, Workbenches |
| <b>Installation Method</b>                                     | Loose lay                                                       |
| <b>Cleaning Method</b>                                         | Brush/mop the top surface                                       |
| <b>Fire Tested to</b>                                          | BS EN 13501-1 Class Dfl - s1                                    |
| <b>Guarantee</b>                                               | 1 year when used in a dry environment                           |
| <b>Adhesive recommended by F.Ball for permanent bond</b>       | F44                                                             |
| <b>Tackifier recommended by F.Ball</b>                         | F41                                                             |
| <b>Adhesive recommended by F.Ball for heavy-duty/wet areas</b> | F74, F81, F84                                                   |

## Additional Information



Orthomat Fire Test BS EN 13501



Orthomat Fire Test EN ISO 11925



Orthomat Fire Test EN ISO 9239

